NORDICFENDER®

Doc. no.:TDS-NF-P-2030-80-SDoc. name:Technical data sheet NF-P-2030-80-SDescription:2.0 x 3.0 m sling type fender



Fender			
 Type Model Fender body / Diamet Fender / Total diamet Length Total Weight Work Pressure Test Pressure 		Pneumatic Fender NF-P-2030-80-S 2000 mm 2000 mm 3000 mm 572 kg 80 kPa 250 kPa	
Performance			
 Energy Absorption (at 60 % deflection) Reaction Force (at 60 % deflection) Hull Pressure (at 60 % deflection) 		369 kNm 986 kN 174 kPa	
Drawing Reference			
• GA		GA-NF-P-2030-50-S	
OPTIONALS:		Color: Grey, green, red, white	
		Tyre net: Heavy duty aircraft chain & tyre net	
Certified Quality			
Applicable rules and regulations		ISO 17357-1:2014	
Warranty			
Warranty	month from the buye	ility for defects is limited to defects which appear within a period of 12 r's further delivery of the equipment to the buyer's customer as an e ship, or within a maximum of 18 month from delivery to the buyer,	

integrated part of the ship, or within a maximum of 18 month from delivery to the buyer, whichever comes first.

Edition date	Revision	Reason for issue	Prep. by	Issued by	Appr. by
09.08.2021	0	First issue	ÅL	ÅL	ÅL

Legal notice: This document and its content is the property of Nordic Fender AS and may not be reproduced, transferred or issued to others without written permission.

Page 1 | 1