NORDICFENDER® MIND THE GAP

TDS-NF-P-2555-50-C Doc. no.: Doc. name: Technical data sheet NF-P-2555-50-C 2.5 x 5.5 m with chain & tyre net Description:



Fender

| Pneumatic Fender |
|--------------------------------|
| NF-P-2555-50-C |
| 2500 mm |
| 2900 mm |
| 5500 mm |
| 2840 kg (Body/CTN = 1275/1565) |
| 50 kPa |
| 250 kPa |
| L75 kPa |
| |

Performance

| • | Energy Absorption (at 60 % deflection) | 943 kNm |
|---|--|---------|
| • | Reaction Force (at 60 % deflection) | 2019 kN |
| • | Hull Pressure (at 60 % deflection) | 148 kPa |

Drawing Reference

| 0 | |
|------------|--|
| • GA | GA-NF-P-2555-50-C |
| OPTIONALS: | Color: Grey, green, red, white Tyre net: Heavy duty aircraft chain & tyre net |
| | |

Certified Quality

Applicable rules and regulations

ISO 17357-1:2014

Warranty

Warranty

Nordic Fender AS liability for defects is limited to defects which appear within a period of 12 month from the buyer's further delivery of the equipment to the buyer's customer as an integrated part of the ship, or within a maximum of 18 month from delivery to the buyer, whichever comes first.

| Edition date | Revision | Reason for issue | Prep. by | Issued by | Appr. by |
|--------------|----------|------------------|----------|-----------|----------|
| 09.08.2021 | 0 | First issue | ÅL | ÅL | ÅL |
| | | | | | |

Legal notice: This document and its content is the property of Nordic Fender AS and may not be reproduced, transferred or issued to others without written permission.

Page 1 | 1