## NORDICFENDER®

Doc. no.:TDS-NF-P-4570-80-CDoc. name:Technical data sheet NF-P-4570-80-CDescription:4.5 x 7.0 m with chain & tyre net



## Fender

<ul> <li>Type</li> <li>Model</li> <li>Fender body / Diameter</li> <li>Fender / Total diameter</li> <li>Length</li> </ul>		Pneumatic Fender NF-P-4570-80-C 4500 mm 4900 mm 7000 mm
<ul><li>Total Weight</li><li>Work Pressure</li></ul>		8976 kg (Body/CTN = 4385/4591) 80 kPa
<ul><li>Test Pressure</li><li>Safety Valve Pressure</li></ul>		300 kPa 230 kPa
Performance		
<ul> <li>Energy Absorption (at 60 % deflection)</li> <li>Reaction Force (at 60 % deflection)</li> <li>Hull Pressure (at 60 % deflection)</li> </ul>		5159 kNm 5873 kN 198 kPa
Drawing Reference		
• GA		GA-NF-P-4570-50-C
OPTIONALS:		Color: Grey, green, red, white
		Tyre net: Heavy duty aircraft chain & tyre net
Certified Quality		
Applicable rules and regulations		ISO 17357-1:2014
Warranty		
Warranty	Nordic Fender AS liab	ility for defects is limited to defects which appear within a period of 12

Nordic Fender AS liability for defects is limited to defects which appear within a period of 12 month from the buyer's further delivery of the equipment to the buyer's customer as an integrated part of the ship, or within a maximum of 18 month from delivery to the buyer, whichever comes first.

Edition date	Revision	Reason for issue	Prep. by	Issued by	Appr. by
09.08.2021	0	First issue	ÅL	ÅL	ÅL

Legal notice: This document and its content is the property of Nordic Fender AS and may not be reproduced, transferred or issued to others without written permission.

Page 1 | 1